

Distribution and Aftermarket

Complete portfolio of refrigeration compressors, condensing units and service parts



**PROFESSIONAL
KITCHEN**



BAKERY



SUPERMARKET



**GROCERY
STORES**

Compressors



R-134a, R-404A,
R-290, Blend

Condensing Units



R-134a, R-404A

Embraco Service Parts



Relay, Overload,
Capacitor and More

MODEL	FAMILY	VOLTAGE & FREQUENCY	REFRIGERANT*	CAPACITY**	APP	HP	MAIN COMMERCIAL APPLICATION	KEY BENEFITS	NOTES
EMC3121U	EM	115-127V / 60Hz 220-240V / 50-60Hz 220-240V / 50Hz	R290	1015Btu/h 97W	LBP MBP	1/4 HP	Beverage Cooler, Chest Freezers, Reach-in refrigerator, Horizontal Freezers; Undercounters; Prep Tables; Back Bars, Beverage Dispenser; Fountain; Medical Refrigerator (Undercounter and Upright), Medical Incubator, Coffins Islands (MBP)	Compact Size Low Noise and Vibration Energy savings Natural refrigerants	**Data for 60Hz. **Test conditions ASHRAE LBP32
EMC3140U	EM	115-127V / 60Hz 220-240V / 50Hz	R290	2027Btu/h 594W	LBP MBP	1/2 HP	Beverage Cooler, Chest Freezers, Reach-in refrigerator, Horizontal Freezers; Undercounters; Prep Tables; Back Bars, Beverage Dispenser; Fountain; Medical Refrigerator (Undercounter and Upright), Medical Incubator, Coffins Islands (MBP)	Compact Size Low Noise and Vibration Energy savings Natural refrigerants	**Data for 60Hz. **Test conditions ASHRAE LBP32
FFU130HAX	FFU	115-127V / 60Hz 220-240V / 50-60Hz 220-240V / 50Hz	R134a	1250Btu/h 366W	LBP MBP	1/3+ HP	Beverage Coolers, Reach-in refrigerators, Horizontal Freezers; Undercounters; Prep Tables; Back Bars, Beverage Dispensers; Fountains; Coffins Islands (MBP)	Efficient replacement for legacy models (FFI); Sturdiness; Approved to operate with alternative refrigerants (R-513A)	* Also available in R290 (220-240V/50-60Hz; 115-127V / 60Hz) **Data for 60Hz. **Test conditions ASHRAE LBP32
FFU160HAX	FFU	115-127V / 60Hz 220-240V / 50-60Hz 220-240V / 50Hz	R134a	737-15330Btu/h	LBP MBP	1/4+ to 1/2 HP	Service Cases Beverage Coolers Freezers	Efficient replacement for legacy models (FFI); Application Flexibility; Sturdiness	* Also available in R290** Data for 60Hz and refrigerant R134a **Test conditions ASHRAE LBP32
NT2180UV	NT	115-127V / 60Hz 220-240V / 50-60Hz 220-240V / 50Hz	R290	216-450W 3577Btu/h	LBP	1to 1 1/4 HP	Beverage Coolers, Service Cases (Dessert and Butcher), Reach-in Refrigerators and Freezers, Coffins Islands (LBP), Grab N Go Self-Contained, Cold Rooms, Horizontal Freezers; Undercounters; Prep Tables; Back Bars, Blast Chillers, Ice Machines, Medical Freezers (Upright), Medical Ultra Low Temperature	High displacement to operate with natural refrigerant; Applicable for Medical & Scientific ULT refrigerators; Application flexibility (High Starting Torque); IPR valve available	* Also available in R404A (115-127V/60Hz; 220V/50Hz)**Data for 115V / 60Hz. **Test conditions ASHRAE LBP32
UNE0020LGG	UNEK	115V / 60Hz	R404A	1048W 1268Btu/h / 371W	LBP	1/5 HP		Options of features package; Standard and UL compliant components; Coil U-bend protection; Discharge tube protection; Sturdy packaging; Nitrogen holding - Factory charged	
UNT0100MZG	UNTU	115V / 60Hz	R134a	7607Btu/h / 2229W	MBP	1 HP	Bottle Cooler Service Cases (Dessert and Butcher) Reach-in Refrigerators and Freezers Coffins Islands (LBP) Grab N Go Self Contained Blast Chillers		**Test conditions ARI LBP
UNT0125MGD	UNTU	208-230V / 60Hz	R404A	11041Btu/h / 3235W	MBP	1 1/4 HP		Options of features package; Standard and UL compliant components; Coil U-bend protection; Discharge tube protection; Sturdy packaging; Nitrogen holding - Factory charged	



Download Embraco
TOOLBOX APP