ErP Report

(For ErP Directive 2009/125/EC, COMMISSION REGULATION (EU) No 327/2011)

■Basic Information of FAN

Model name	G1276X50B9YP-xx
Fan type	AXIAL FAN

Nidec Servo Co., Ltd. 2016/12/6 R&D Dept.I Report No K102160006

Approval : T.Shiraishi Preparation : T.Banba

■ Specification Information of FAN

Specification information of FAN		
No.	Item	Data
1	$\eta_{ ext{ target}}$	28.5%
2	Overall efficiency($\eta_{ m e}$)	50.5%
3	Measurement category (A-D)	A
4	Efficiency category (static or total)	Static
5	Efficiency grade at optimum energy efficiency point	N=40
6	VSD is integrated within the fan	Yes
7	Year of manufacture	From 2017
8	Manufacturer's name and place of manufacturer	NIDEC VIETNAM CORPORATION
		Ho Chi Minh City, Vietnam
9	Product's Part number	G1276X50B9YP-xx
10-1	Rated motor power input(s) (kW) at optimum energy efficiency	0.151 kW
10-2	Rated motor flow rate(s) at optimum energy efficiency	174.6 CFM
10-3	Rated motor pressure(s) at optimum energy efficiency	3.3 inch-H2O
11	Rated motor rotations per minute at optimum energy efficiency	11600 RPM
12	Specific ratio	0.984
13	Information relevant for facilitating disassembly, recycling or disposal at end-of-life	Method of disassembly :
		by needle nose pliers
		Materials that can be recycled:
		Impeller PPS-GF40%
		Housing Diecast
14	Information relevant to minimise impact on the environment and ensure optimal life expectancy as regards installation, use and maintenance of the fan	Meeting Rohs requirement. Impeller and Housing can be recycle.
15	Description of additional items used when determining the fan energy efficiency, such as ducts.	There is no obstacle at inlet and outlet of fan to measure performance.

■P-Q Performance



