

FGE-X Digital Force Gauges

Digital Force Gauges with 180° reversible display & dual labeled keypad for both push, pull applications

The Series FGE-X Digital Force Gauges combine a rugged, ergonomic and compact design with exceptional accuracy to provide a solid force testing instrument. These instruments are utilized in a variety of applications such as, incoming quality inspection, finished goods testing, R&D or almost any portable or force stand testing requirement.

Simple one button adjustment changes units of measure, while pressing the peak button quickly produces the highest recorded value during the test. The 180° reversible display combined with the adjustable force direction and dual labeled keypad enable the FGE-X to excel in both compression and tension applications in any direction. Models are available from 0.5 lbs to 100 lb ranges providing a large offering for various testing requirements.

Typical applications include wallboard, wire pull, wire crimps, trigger pull, brake pedal, aerospace ceramic, springs, food ripeness, corrugated paper strength, blister pack, medical component, muscle strength, ergonomic testing, adhesives, syringe plunger, needle sharpness and many more.



Features

- 1000 Hz Sample Rate provides faster sampling producing better resolution and more accurate results
- Ideal for strict tolerances with its high accuracy $\pm 0.2\%$ F.S.
- Measure and record compression and tension tests- permits true "push-pull" testing
- 180° Reversible display and dual printed keypad allows usage as a portable gauge or mounted upside down on a test stand
- 1 million operation load cell with superior overload protection provides a long-life, damage free product
- Rugged, ergonomic die cast aluminum construction allows usage on production floor
- Variable display response rate aids viewing readings
- Quick retrieval of peak measurement with a single push button
- Flexible user preference with one button selection of engineering units
- Dual power capable with rechargeable battery or AC line voltage
- CE Mark



FGE-X with Accessories
in Protective Carrying Case

FGE-X Specifications

FGE-X Model	FGE-0.5X	FGE-1X	FGE-2X	FGE-5X	FGE-10X	FGE-20X	FGE-50X	FGE-100X
Capacity	8 oz 0.5 lb 200.0 g 2.000 N	16 oz 1 lb 500.0 g 5.000 N	32 oz 2 lb 1,000 g 10.00 N	5 lb 2.000 Kg 20.00 N	10 lb 5.000 Kg 50.00 N	20 lb 10.00 Kg 100.0 N	50 lb 20.00 Kg 200.0 N	100 lb 50.00 Kg 500.0 N
Resolution	0.01 oz 0.001 lb 0.1 g 0.001 N	0.01 oz 0.001 lb 0.1 g 0.001 N	0.01 oz 0.001 lb 1 g 0.01 N	0.001 lb 0.001 Kg 0.01 N	0.01 lb 0.001 Kg 0.01 N	0.01 lb 0.01 Kg 0.1 N	0.01 lb 0.01 Kg 0.1 N	0.1 lb 0.01 Kg 0.1 N
Accuracy	±0.2% F.S.							
Display	4-Digit LCD, 0.5" (12 mm) high, Units 0.29" (7 mm). Reversible by the push of a button. Minus sign for tension							
Display Update	0.05, 0.1, 0.2, 0.3, 0.5, 1 sec							
Sampling Rate	1000 Hz							
Overload	200% of F.S. (200 lb.: 150% F.S.)							
Power	Rechargeable Ni-Cad battery or AC adapter/charger							
Auto Power Shut-Off	Yes (not active if adapter/charge is in use)							
Battery Charge	12 hours (when fully charged)							
Recharge Time	Approximately 18 hours when fully discharged							
Temperature Range	32 - 104°F (0 - 40°C)							
Dimensions	5.8 x 3 x 1.5" (147 x 75 x 38 mm)							
Product Weight	Approx. 1 lb (450 g)							
Package Weight	Approx. 2.25 lb (1.02 kg) for 0.5 lb and 1 lb ranges; 2.4 lb (1.09 kg) for 2 to 100 lb ranges							
Certification	CE							
Included Accessories	AC adapter/charger, carrying case, hook, chisel, flat head, notched head, hanger, cone head, thread Adapter, extension rod							

Ordering Details

FGE-0.5X	0.5 lb capacity digital force gauge
FGE-1X	1 lb capacity digital force gauge
FGE-2X	2 lb capacity digital force gauge
FGE-5X	5 lb capacity digital force gauge
FGE-10X	10 lb capacity digital force gauge
FGE-20X	20 lb capacity digital force gauge
FGE-50X	50 lb capacity digital force gauge
FGE-100X	100 lb capacity digital force gauge
NIST-FG	NIST traceable certificate of calibration for ranges from 0.5 to 100 lbs
FGE-PT100	100 lb capacity FGE-X in ergonomic testing kit. Kit includes all of the standard FGE-X accessories but comes with larger, heavy duty case and adds padded ERGO accessories, handle, and NIST traceable certificate

DISTRIBUTED BY:

Accessories

FG-M4ADP	Standard adapter set with M4 threads for ranges 0.5 lb and 1 lb. Includes: chisel, cone, flat head, notched head, hook, extension rod
FG-M4CL	Chisel adapter with M4 thread for ranges 0.5 lb and 1 lb.
FG-M4CN	Cone head adapter with M4 thread for ranges 0.5 lb and 1 lb.
FG-M4FL	Flat head adapter with M4 thread for ranges 0.5 lb and 1 lb.
FG-M4GV	Notched head adapter with M4 thread for ranges 0.5 lb and 1 lb.
FG-M4HK	Hook adapter with M4 thread for ranges 0.5 lb and 1 lb.
FG-M4RD	Extension rod adapter with M4 thread for ranges 0.5 lb and 1 lb.
FG-M6ADP	Standard adapter set with M6 threads for ranges 2 lb to 200 lb. Includes: chisel, cone, flat head, notched head, hook, extension rod
FG-M6CL	Chisel adapter with M6 thread for ranges 2 lb to 200 lb.
FG-M6CN	Cone head adapter with M6 thread for ranges 2 lb to 200 lb.
FG-M6FL	Flat head adapter with M6 thread for ranges 2 lb to 200 lb.
FG-M6GV	Notched head adapter with M6 thread for ranges 2 lb to 200 lb.
FG-M6HK	Hook adapter with M6 thread for ranges 2 lb to 200 lb.
FG-M6RD	Extension rod adapter with M6 thread for ranges 2 lb to 200 lb.
FG-09V120UC	Universal charger adapter for 120/240V AC
ERGO-KIT	Padded accessory kit for ergonomic testing
FG-HANDLE	Handle adapter for larger loads

A Nidec Group Company

SHIMPO All for dreams

NIDEC-SHIMPO AMERICA CORPORATION • Phone: (800) 237-7079 • Fax: (630) 924-0342 • www.shimpoint.com